

TriBor30 SPECIFICATIONS

POWER PACK

- Skid Mount, 200 HP Diesel Engine
- 24 VDC Wiring, CAN Bus Plus1 Controller
- Constant Hydraulic Oil Cooler System
- 10 Micron Filtration System
- Independent Pumps
- Rotation (Closed Loop) 6000 PSI
- Thrust (Open Loop) 5000 PSI
- Auxiliary 5000 PSI

ROTATION CIRCUIT

- Rotary Gearbox
- 33,741 Ft. Lbs. Max Torque
- 3 Speed, 100 RPM Max
- Boost Feature

THRUST CIRCUIT

- Cylinder / Centerline Push
- 282,743 Lbs. Push
- 186,532 Lbs. Pull
- Rack and Pinion-31,104 Lbs.
- 90 FPM Max

BREAKOUT WRENCHES

- Removable, Floating
- Dual Open Top Clamps
- Adjustable Clamp Force

MUD SYSTEM

- 9 GPM Max
- 750 PSI Max
- 300 or 500 Gallon Capacity
- Mixer Type-9" Prop

FEATURES

- Wireless Remote Controlled
- ABM, GBM, and HDD Operation Mode
- Danfoss Plus1 Operation Controller with Self Diagnostics
- ADM-Automatic Drill Modes
- Optional On-board Crane
- Extendable Footprint